

4" Encapsulated Motors



4" Super Stainless 3 Phase

Submersible Motors Quality in the Well

These 4" encapsulated three phase motors, manufactured in ISO 9001 certified facilities, are built for dependable operation in 4" diameter or larger water wells. The motor offers you a maintenance free long life submersible pump application.

The motor is filled with a special FES93 fluid, providing frost protection down to -40°C storage temperature.

A special diaphragm ensures pressure compensation inside the motor.

Product advantages standard:

- Hermetically sealed stator. anti track, self healing stator resin prevents motor burn out
- High efficiency electrical design (low operation cost, cooler winding temperature)
- Removable "Water Bloc™" lead connector
- Cable material according to drinking water regulations (KTW approved)
- Water lubricated radial and thrust bearings
- All motors prefilled and 100% tested. Non contaminating, FES93-filled design

Brackish Water version Specifications:

- For use in water that has more salinity than fresh water, but not as much as seawater.
- The novel Franklin Electric Brackish Water Motor proposes a cost-effective solution wherever standard 4" motors are not giving sufficient service life

Heat Pump version Specifications:

- Many modern heating systems extract heat that is stored in aquifer / river water. Such so-called two-pit or open systems require low-power, high efficiency 3-phase submersible motors. To meet the demands of this niche market, Franklin Electric has developed a special 4" encapsulated submersible motor optimized for shallow settings and low power consumption available in 0,25kW; 380-415V/50Hz.



Pollution Recovery version Specifications:

- Fluorelastomere (Viton®) rubber parts
- Special Polyurethane (PUR) lead assemblies
- 304 graded stainless steel as standard, 316SS as an option

Technical Specifications Standard Motor:

- 0,37 - 7,5kW
- 4" NEMA flange
- Degree of protection: IP68
- Insulation: Cl. B
- Rated ambient temp.: 30°C
- Cooling flow: min. 8cm/s
- Starts/h: 20
- Mounting: vertical/horizontal
- Standard Voltage: 380-415V/50Hz, 460V/60Hz
- Voltage tolerance 50Hz: -10% / +6% U_N [380-415V = (380-10%) – (415+6%)]
- Voltage tolerance 60Hz: $\pm 10\% U_N$
- Motor protection: Select thermal overloads according to EN 60947-4-1, Trip time <10 s at $5 \times I_N$

Options

- Motor cable VDE / ACS / KTW approved (1,5m; 2,5m; special lengths available)
- Motors with factory- installed lead in Single Packing
- Special voltages on request
- YΔ - start (pos. of cables 90°) in motors 316SS on request
- Motor complete in AISI 316SS with SiC seal

3~ 4" Encapsulated Motors 400V / 50Hz											
P _N [kW]	Thrust F [N]	U _N [V]	n _N [min ⁻¹]	I _N [A]	I _A [A]	η [%]	cos φ [%]	T _N [Nm]	T _A [Nm]	L [mm]	m [kg]
0,37	3000	400	2870	1,1	5,41	66	0,74	1,22	3,00	214,2	7,2
0,55	3000	400	2870	1,6	7,4	68	0,74	1,82	4,20	228,2	7,7
0,75	3000	400	2865	2,0	10,6	70	0,77	2,49	6,70	248,2	8,7
1,1	3000	400	2850	2,8	16,0	74	0,78	3,67	11,33	282,6	10,2
1,5	3000	400	2855	3,9	20,7	73	0,78	5,00	14,10	306,6	11,2
2,2	4000	400	2845	5,5	29,8	75	0,77	7,37	22,0	338,6	12,6
	6500*	400	2845	5,5	29,8	75	0,77	7,37	22,0	422,2	15,0
3,0	4000	400	2845	7,5	42,0	76	0,77	10,06	31,93	393,6	15,0
	6500*	400	2845	7,5	42,0	76	0,77	10,06	31,93	477,2	17,0
3,7	6500*	400	2840	9,0	52,3	78	0,78	12,5	41,5	520,2	19,1
4,0	6500*	400	2840	9,9	57,0	78	0,77	13,4	44,0	543,2	20,0
5,5	6500*	400	2865	12,6	77,2	79	0,81	18,3	56,5	652,5	26,6
7,5	6500*	400	2855	17,1	99,3	79	0,81	25,1	73,1	730,5	30,6

* High Thrust Version

